

### **Product Information**

3U CompactPCI® IPC

# **CRB-BLUELINE Small Computer Systems**

Document No. 3661 • Last Edited 18 April 2017



CRB-BLUELINE Small Expandable Systems

Rugged, expandable, economic - the new CRB-BLUELINE series of miniature CompactPCI®

IPC systems from EKF is suitable for all industrial requirements, even under harsh conditions. The small rack is built of high-quality 19-inch components. With its low dimensions of only 172x132x208mm (3U/30HP), the BLUELINE provides space for up to five CompactPCI® modules (single size Eurocard style). The BLUELINE systems include an industrial grade removable power supply.

EKF offers a wide range of scalable CPU boards suitable for the BLUELINE to choose from, beginning with power optimized Intel® Atom™ processor series, up to the Intel® Core™ i7 high performance CPU.

A mass storage device, either 2.5- or 1.8-inch SSD, or a CompactFlash (option CFast) card, is integral part of the CPU module. Cooling by natural convection is already sufficient for low power processor boards.



CRB-BLUELINE with Fan Unit for High Performance CPU Usage

Available as accessories, the BLUELINE can be equipped with wall or bottom mount brackets. A silent 120mm x 120mm cooling fan unit is provided as an option for such high performance CPU boards which require forced convection.

When combined with a CompactPCI CPU card such as the PC3-ALLEGRO, a BLUELINE system supersedes entirely an industrial PC. Another three CPCI slots are available for application specific system expansion. Thanks to the modular, non-proprietary concept, a BLUELINE system can be reconfigured or upgraded in just a few minutes, reducing potential breakdown times to a minimum.

The overall reliability of any system depends in particular on the quality of its power supply unit. BLUELINE systems are provided with a removable, high-grade industrial PSU from a leading German manufacturer. As of current, the CRB-BLUELINE systems can be equipped with PSU versions suitable either for 120/230VAC or 24VDC power line input (automotive applications). The BLUELINE is a long-time available and scalable IPC system, combining high reliability and small size with an affordable price, thus forming the better alternative compared to many other PC based solutions. Please request for custom specific versions, tailored to your individual needs. Quality pays, its up to you!



CRB-BLULINE w. Wall Mount Brackets

Technical Summary	
General	3U rack/enclosure 30HP, shielded, equipped with tip up feet, ready for installation of 1 x system slot CompactPCI CPU card 3U/4HP (w/o companion board) or 8HP (with companion board), 3 x peripheral slot CPCI cards 3U/4HP (blind panels included), equipped with 1 x CPCI PSU 3U/10HP
Dimensions	<ul> <li>~ 172mm (width) x 132mm (height) x 208mm (depth), measured w/o tip up feet or accessories</li> <li>~ 166mm (height) with top mount fan unit</li> </ul>
CompactPCI Bus	<ul> <li>1 x P1/P2 system slot, right side (red card rails)</li> <li>3 x P1 peripheral slots (blind panels included)</li> <li>CompactPCI 32-bit, +5V VIO (+3.3V VIO on request)</li> <li>1 x M connector for PSU slot, left side</li> </ul>
PSU (AC Version)	<ul> <li>Removable, 3U/10THP, permanently short circuit proof, over-voltage protection primary/secondary</li> <li>Ambient temperature -25°C +70°C (derating 2%/K above 50°C), protected against overheating</li> <li>Line input 90-138VAC/187-264VAC 50/60Hz (changing automatically), input connector IEC320/C5</li> <li>Outputs +5V/8A, +3.3V/10A, M24/8 connector matching the backplane, SELV according to EN 60950</li> <li>Power cord and fastener bracket included</li> </ul>
Fan Unit (optional)	<ul> <li>120mm x 120mm, silent type, 5V DC, 2.1W, air flow 1.66m³/min 58.6CFM, 1850rpm, 29dbA</li> <li>provided with CRB-4(5,6)-BLUELINE</li> </ul>
EC Regulations	► EN55022, EN55024, EN60950-1 (UL60950-1/IEC60950-1)  ► 2002/95/EC (RoHS)
Accessories (optional)	<ul><li>Wall mount brackets</li><li>Bottom mount brackets</li></ul>

subject to changes



CRB-BLUELINE with Wall Mount Brackets



AC Power Cord Fastener



CRB-BLUELINE with DC Power Supply



CRB-BLUELINE Custom Specific

Ordering Information	
Order-No.	Short Description
CRB-1-BLUELINE	Rack 3U/30HP $\sim$ 172mm (width) x 132mm (height) x 208mm (depth), with CompactPCI® backplane, with removable power supply 70W 120/230VAC
CRB-2-BLUELINE	similar to CRB-1-BLUELINE, with removable PSU 70W 24VDC
CRB-4-BLUELINE	Rack 3U/30HP $\sim$ 172mm (width) x 166mm (height) x 208mm (depth), with top mount fan unit, with CompactPCI® backplane, with removable power supply 70W 120/230VAC
CRB-5-BLUELINE	similar to CRB-4-BLUELINE, with removable PSU 70W 24VDC
www.ekf.com/liste/liste_20.html#CRB	

www.ekf.com/c/csys/crb/crb\_e.html

For detailed information regarding suitable CPU boards please visit

www.ekf.com/c/ccpu/ccpu.html www.ekf.com/p/plus.html www.ekf.com/s/serial.html

© EKF -7- ekf.com



# Beyond All Limits: EKF High Performance Embedded

EKF Elektronik GmbH Philipp-Reis-Str. 4 (Haus 1) Lilienthalstr. 2 (Haus 2) 59065 HAMM Germany



